

## Samtec Optimized Flex Lengths

Product Series	Standard Flex Length	Maximum Flex Length for Optimized Cost
HFEM-DP	3.00" (76,20mm)	3.175" (80,65mm)
HFEM-SE	3.00" (76,20mm)	3.175" (80,65mm)
HFEM2-DP	3.00" (76,20mm)	3.175" (80,65mm)
HFEM2-SE	3.00" (76,20mm)	3.175" (80,65mm)
HFHM-DP	3.00" (76,20mm)	3.175" (80,65mm)
HFHM2-DP	3.00" (76,20mm)	3.175" (80,65mm)
HFHM2-SE	3.00" (76,20mm)	3.175" (80,65mm)
HFEM-DP	5.00" (127mm)	5.40" (137,16mm)
HFEM-SE	5.00" (127mm)	5.40" (137,16mm)
HFEM2-DP	5.00" (127mm)	5.40" (137,16mm)
HFEM2-SE	5.00" (127mm)	5.40" (137,16mm)
HFHM-DP	5.00" (127mm)	5.40" (137,16mm)
HFHM2-DP	5.00" (127mm)	5.40" (137,16mm)
HFHM2-SE	10.00" (254mm)	10.00" (254mm)
HFEM-DP	10.00" (254mm)	10.00" (254mm)
HFEM-SE	10.00" (254mm)	10.00" (254mm)
HFEM2-DP	10.00" (254mm)	10.00" (254mm)
HFEM2-SE	10.00" (254mm)	10.00" (254mm)
HFHM-DP	10.00" (254mm)	10.00" (254mm)
HFHM2-DP	10.00" (254mm)	10.00" (254mm)
HFHM2-SE	10.00" (254mm)	10.00" (254mm)
TFMDL (05 positions)	10.00" (254mm)	16.40" (416,56mm)
TFMDL (25 positions)	3.00" (76,20mm)	3.10" (78,74mm)
TFMDL (50 positions)	5.00" (127mm)	5.50" (139,70mm)