

ECN-372758 12/9/2019




TABLE 2							
No OF POSITION	"A"	"B"	"C"	"D"	"E"	"F"	"G"
-5	6.00 [0.236]	2.00 [0.079]	9.10 [0.358]	5.15 [0.203]	10.20 [0.402]	9.10 [0.358]	5.15 [0.203]
-10	8.50 [0.335]	4.50 [0.177]	11.60 [0.457]	7.65 [0.301]	12.70 [0.500]	11.60 [0.457]	7.65 [0.301]
-20	13.50 [0.531]	9.50 [0.374]	16.60 [0.654]	12.65 [0.498]	17.70 [0.697]	16.60 [0.654]	12.65 [0.498]
-30	18.50 [0.728]	14.50 [0.571]	21.60 [0.850]	17.65 [0.695]	22.70 [0.894]	21.60 [0.850]	17.65 [0.695]
-40	23.50 [0.925]	19.50 [0.768]	26.60 [1.047]	22.65 [0.892]	27.70 [1.091]	26.60 [1.047]	22.65 [0.892]
-50	28.50 [1.122]	24.50 [0.965]	31.60 [1.244]	27.65 [1.089]	32.70 [1.287]	31.60 [1.244]	27.65 [1.089]


NOTE:

- ALL DIMENSIONS ARE SYMMETRIC ABOUT THE CENTERLINE.
 CONNECTOR ENVELOPE DIMENSIONS: OTHER COMPONENTS PLACED ON PCB SHALL AVOID THIS ZONE.
 FOR APPLICATIONS REQUIRING TWO OR MORE CONNECTORS PER BOARD, CONTACT IPG@SAMTEC.COM.
 FOR APPLICATIONS OF LSHM-105-01-X-RH REQUIRING INVERTED REFLOW SOLDERING, USE OF AN EPOXY

ADHESIVE IS RECOMMENDED.

PROPRIETARY NOTE THIS DOCUMENT CONTAINS CONFIDENTIAL AND PROPRIETARY INFORMATION AND ALL DESIGN, MANUFACTURING, REPRODUCTION, USE, PATENT RIGHTS AND SALES RIGHTS ARE EXPRESSLY RESERVED BY SAMTEC, INC. THIS DOCUMENT SHALL NOT BE DISCLOSED, IN WHOLE OR PART, TO ANY UNAUTHORIZED PERSON OR ENTITY NOR REPRODUCED, TRANSFERRED OR INCORPORATED IN ANY OTHER PROJECT IN ANY MANNER WITHOUT THE EXPRESS WRITTEN CONSENT OF SAMTEC. INC.





F:\dwg\misc\mktg\footprnt\LSHM-1XX-XX-RH-A-X-X-XX-FOOTPRINT.SLDDRW

REVISION G

RECOMMENDED STENCIL LAYOUT FOR LSHM-1XX-XX-X-RH-A-X-X-TR

